




SMD Square Air Coil

SHAPE AND DIMENSIONS(UNIT:mm):



RECOMMENDED PATTERNS:



Eastever P/N	M1	M2	M3	M4	M5	M6
UCE1111-27~30NJ	2.67±0.254	2.67±0.127	2.79±0.127	2.29	3.05	1.02
SSAC1111-33~39NJ	2.92±0.254	2.67±0.127	2.79±0.127	2.54	3.05	1.02
SSAC1111-43~47NJ	3.30±0.254	2.67±0.127	2.79±0.127	2.79	3.05	1.02
SSAC1515-Series	4.06±0.254	3.56±0.178	3.73±0.178	3.56	4.45	1.78
SSAC2222-Series	5.21±0.381	5.46±0.254	5.69±0.254	4.70	6.35	2.16
SSAC2929-R33J	10.29±0.381	7.49±0.254	7.24±0.254	9.53	8.26	2.29
SSAC2929-R36J	11.30±0.381	7.49±0.254	7.24±0.254	10.54	8.26	2.29
SSAC2929-R39J	12.32±0.381	7.49±0.254	7.24±0.254	11.56	8.26	2.29
SSAC2929-R43J	13.21±0.381	7.49±0.254	7.24±0.254	12.45	8.26	2.29
SSAC2929-R50J	14.00±0.381	7.49±0.254	7.24±0.254	13.21	8.26	2.29

Electrical Characteristics @25 °C:

Eastever P/N	Inductance (nH)	Q (MIN)	Test Freq (MHz)	DCR MAX (mΩ)	SRF (GHz) TYP	Rated current(A) MAX	Coilcraft P/N
SSAC3333-49PL	49	422	622	: 08	408	707	1111SQ-27N
SSAC3333-52PL	52	422	622	: 06	406	707	1111SQ-30N
SSAC3333-55PL	55	422	622	: 07	405	60	1111SQ-33N
SSAC3333-58PL	58	422	622	: 0	405	60	1111SQ-36N
SSAC3333-5; PL	5;	422	622	320	404	60	1111SQ-39N
SSAC3333-65PL	65	422	622	320	404	606	1111SQ-43N
UCE3333-69PL	69	422	622	3305	404	606	1111SQ-47N
UCE3737-69PL	69	452	622	8057	30 9	60 2	1515SQ-47N
UCE3737-8; PL	8;	452	622	: 082	4055	7072	1515SQ-68N
UCE3737-; 4PL	: 4	452	622	: 062	30;	7082	1515SQ-82N
UCE4444-; 2PL	: 2	362	72	7072	307	702	2222SQ-90N
UCE4444-T33L	332	362	72	8072	302	702	2222SQ-111
UCE4444-T35L	352	362	72	9072	302	7062	2222SQ-131
UCE4444-T38L	382	362	72	: 047	302	702	2222SQ-161
UCE4444-T3: L	3: 2	362	72	: 072	302	702	2222SQ-181
SSAC4444-T44L	442	362	72	330	302	702	2222SQ-221
SSAC4444-T49L	492	362	72	3407	20 2	6052	2222SQ-271
SSAC4444-T52L	552	372	72	350	204	502	2222SQ-301
SSAC4; 4; -T55L	552	3: 2	72	3407	2088	602	2929SQ-331
SSAC4; 4; -T58L	582	3: 2	72	3507	2084	6072	2929SQ-361
SSAC4; 4; -T5; L	5; 2	3: 2	72	3607	207;	6062	2929SQ-391
SSAC4; 4; -T65L	652	3: 2	72	3707	2077	6042	2929SQ-431
SSAC4; 4; -T72L	722	3: 2	72	3807	2072	6052	2929SQ-501

CHARACTERISTIC CURVES

